


MI1250 power amplifier

- The MI1250 12-Channel Digital Amplifier can distribute pristine music playback in multiple rooms in your home.
- Delivers 50 Watts into 8 Ohm speakers or 90 Watts into 4 Ohm speakers via highly sophisticated closed loop digital switching amplifiers that are paired with extremely robust power supplies to produce performance levels that are rarely achieved in distributed audio.
- Installer-friendly physical dimensions and is 2U rack mountable via the included mounting ears (ears are removable for non-rack installations).
- A highly efficient Class D amplifier, it does not require noisy cooling fans to maintain nominal operating temperature.
- Multi-color LED indicators display the status of each channel. Features unbalanced inputs plus 2-pole Phoenix style push-in speaker terminals for each channel.
- Includes volume controls for volume balancing, along with 2 digital audio inputs (either coax or optical) that can be bussed, and channel summing circuits for easy mono signal distribution.
- Other features included: Power Guard® signal overload technology that prevents overdriving the speakers; Sentry Monitor™ short-circuit protection that disengages the output stage before current exceeds safe operating levels; BUS input & outputs to easily distribute a stereo signal to multiple outputs and/or multiple amplifiers; individual channel inputs; 12 Volt triggering capabilities; and eco-friendly on/off signal sensing.



Pristine Music Playback in Multiple Rooms.

McIntosh®

LEGENDARY PERFORMANCE®

www.mcintoshlabs.com

MI1250 power amplifier

Power Output:

50 Watts into 8 Ohm speakers
90 Watts into 4 Ohm speakers

Total Harmonic Distortion:

0.05% maximum from 20Hz to 20kHz

Signal to Noise Ratio:

85dB

Dynamic Headroom:

8 Ohms: 2.1dB
4 Ohms: 3.3dB

Damping Factor:

8 Ohms: >65
4 Ohms: >32

Frequency Response:

+0, -0.5dB from 20Hz to 20kHz

Inputs:

12 Unbalanced
2 Digital (coax or optical)
2 BUS

BTU Rating:

900 BTU/h

Overall Dimensions (W x H x D):

17-1/2" (44.45cm) (19" (48.3cm with
mounting ears)) x 4-5/16" (11cm)
x 2 1" (53.3cm)

Weight:


22 lbs (10kg) net,
38.4 lbs (17.4kg) in shipping carton

For the Consumer's Protection:

In order to ensure the highest level of customer satisfaction, new McIntosh products may only be purchased from an Authorized McIntosh Dealer; and, with certain limited exceptions may only be purchased over-the-counter or delivered and installed by the Authorized McIntosh Dealer. McIntosh does not warrant, in any way, products that are purchased from anyone who is not an Authorized McIntosh Dealer, or that have had their serial numbers altered or defaced.



Typical McIntosh custom install products installed in an AV rack.



Companion Products

The MCD600 SACD/CD Player, MS500 Music Streamer, WS500 and WS300 In-Wall Loudspeakers, and CS200 In-Ceiling Loudspeaker are logical companions for the MI1250 Power Amplifier. Your Authorized Dealer can provide additional information on other McIntosh product combinations.

To learn more, please call us at 1.800.538.6576.

McIntosh®

LEGENDARY PERFORMANCE®

www.mcintoshlabs.com